


Material Safety Data Sheet

Product Name/Identity:
 "Maxfelt 30"
 Roof Underlayment



MSDS Number: 0106
CAS Number: None
Date Prepared: 12/20/2012
Revised:

SECTION 1 - MATERIAL COMPOSITION AND INFORMATION

| | CasReg# | % |
|----------------------------------|-----------|-------|
| Polypropylene | 9003-07-0 | 50-80 |
| Polyethylene | 9002-88-4 | 27-50 |
| Proprietary UV inhibitors | NE | 2-3 |
| Printing Inks | NE | 0-1 |

NE = Not Established

SECTION 2 - PHYSICAL PROPERTIES

| | | | |
|---|-----------|---|------|
| Vapor Pressure (mm Hg and Temperature) | N/A | Melting Point (degrees F) | >200 |
| Vapor Density (Air = 1) | N/A | Evaporation Rate (Butyl Acetate = 1) | N/A |
| Solubility in Water | INSOLUBLE | Water Reactive | N/A |

SECTION 3 -- FIRE AND EXPLOSION HAZARD DATA

| | | | | | |
|---|---|--|--------------------|-------------------|-------------------|
| Flash Point and Method Used >600°F, COC | Auto-Ignition Temperature >620° F | Flammability Limits in Air N/A | % by Volume | LEL N/A | UEL N/A |
|---|---|--|--------------------|-------------------|-------------------|

Extinguisher Media: FOAM, CO2, DRY CHEMICAL, HALON, WATER

Special Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING - DO NOT RELEASE RUNOFF FROM FIRE CONTROL METHODS TO SEWERS OR WATERWAYS.

Unusual Fire and Explosion Hazards: COMBUSTIBLE MATERIAL WHEN HEATED, MAY BURN IF AN IGNITION SOURCE IS PROVIDED. FUMES MAY EXPLODE IF EMITTED IN AN ENCLOSED ENVIRONMENT WITH AN IGNITION SOURCE.

