

Get the MAX-imum Protection  
**MAXFELT.COM**



- Code Compliance Research Report 0340
- Fire Classification: Class A ASTM E108
- Meets or Exceeds Performance Criteria for ASTM D226 Types I and II
- Meets or Exceeds Performance Criteria for ASTM D4869 Types I, II, III, & IV
- Limited 50 Year Warranty
- For Use Under Metal, Shingles, Shake and Tile Roofs
- 12 Month UV Exposure
- Secondary Weather Protection Layer
- Advanced, Anti-skid Backside Coating
- Enhanced Spunbond Non-woven Walking Surface

	<b>MAX FELT 180</b>
WIDTH (inches)	48 inches
ROLL LENGTH (feet)	250 feet
WEIGHT PER SQUARE (1000 ft <sup>2</sup> )	37 Lbs
THICKNESS ASTM D-1777	12.0 mils
TENSILE TEST ASTM D-5035 (lb/in) D751	MD = 128 CD = 115
TEAR TEST ASTM D-4533 (lbf)	MD = 57; CD = 48
WVTR ASTM D-4869	PASS
PLIABILITY ASTM D-226	PASS
UV EXPOSURE	12 MONTHS
CODE COMPLIANCE AC-188; ASTM D228 ASTM D8257)	PASS CCRR-0340
FIRE CLASSIFICATION (ASTM E108)	PASS
ROLLS / PALLET	36



FBC # FL42142

REPORT# CCRR-0340

TDI APPROVED